

RSL-2701U



Where Quality and Value Reign

TABLE TOP LAMINATOR



Features & Benefits

- **Fast** - Laminates thermal film up to 27" (685 mm) wide at speeds up to 7.9' (2.4 m/min) per minute.
- **Quality**– High quality silicone rollers and digital controls for temperature and speed help deliver a perfect finish.
- **Versatility** -Designed for laminating & encapsulating individual or multiple copies of posters prints, POP signs, training aids, rigid or flexible signage and much more.
- **Easy To Use** - Soft touch digital keypad allows easy operation and function control.
- **Convenient**– Tabletop roll laminator is great for small working areas.

PDS - Pressdown Services Inc.

Tel: (800) 608-4506 (416) 297-7996 Fax: (416) 297-9465

Website: www.pressdown.net Email: sales@pressdown.net

Royal Sovereign International, Inc.

Specifications

Model	RSL-2701U
Power supply	AC120V / 60Hz
Power consumption	1500W
Max laminating width	27 (in) / 685 (mm)
Max laminating speed	7.9 (ft/min) / 2.4 (m/min)
Film thickness	*1-10 (mil) / 25~ 250 (mic)
Ready time	8-9 min
Heating method	Hot Roller
Driving motor	DC geared motor
Temperature control	Digital up to 310°F (155°C)
Speed control	Digital (10 settings)
Transport type	4 Roller
Auto Off/Standby	Yes
Cross cutter	Yes
Document guides	Yes
Hot lamination	Yes
Cold lamination	No
Mounting/foam board	Yes 1/16" (2mm)
Reverse	Yes
Unit weight	110 (lbs) / 50 (kg)
Unit dimensions (W x D x H)	36.2 x 20.5 x 12.6 (in) 920 x 520 x 320 (mm)
Carton weight	132 (lbs) / 60 (kg)
Carton dimensions (W x D x H)	44.5 x 20.7 x 29 (in) 1130 x 527 x 737 (mm)
Warranty	1 year parts & labor (Rollers 6 months)

* 1-10 mil Royal Sovereign film. Other manufacturers may vary.