

# SPD-Eco1630III Specifications

Recording	Capstan
RIP	SDP-RIP 6.0 (Harlequin Eclipse 6.x for Windows 2000/2003/XP)
Light Source	Red Laser Diode (635 nm)
Resolutions	1200, 1500, 1800, and 2400 dpi
Recording Speed	48" (1236 mm) per minute at 1200 dpi 31" (791 mm) per minute at 1500 dpi 22" (552 mm) per minute at 1800 dpi 12" (309 mm) per minute at 2400 dpi
Maximum Recording Width	15.9" (404 mm)
Output Media	Mitsubishi Silver DigiPlate™ Material Polyester: SDP-FR100 .004" (.012 mm) SDP-FRm175 0.008" (.020 mm) Paper: SDP-RR175 0.008" (.020 mm)
Plate Width	9" to 16 5/16" (229 to 414 mm)
Plate Length	8.65" to 22.83" (220 to 580 mm)
Roll Specification	Spec 725
Interface	Fast Wide SCSI (16 bit)
Integrated Eco Processor Processing Solution	Mitsubishi SLM-EAC (Activator) Mitsubishi SLM-EST (Stabilizer)
Tank Capacity	Main Tank Replenishing Bottle Activator.145 gal (0.55 liter) .528 gal (2 liter) Stabilizer.159 gal (0.60 liter) .528 gal (2 liter) Wash-off Water .068 gal (0.26 liter) .264 gal (1 liter)
Output Speed	78 plates/hr at 1200 dpi
Physical Dimensions	W x D x H: 39 3/8" x 31 5/16" x 42 1/8" (1000 x 795 x 1070 mm)
Weight	456 lbs (207 kg)
Power Requirements	100/120 VAC, 15 Amp, 50/60 Hz
Operating Environment	73.4 ± 9°F (23 ± 5°C), 50-70% RH
Options	Integrated Converting Punching Unit /Bell or DS System Differential SCSI Additional page buffer module External Beil Punching Unit

## Value in Vision

The SPD-Eco1630III is one of dozens of innovations that Mitsubishi Imaging brings you. We're the industry leader in polyester plate technology. Our full range of platesetters and consumables enhance your production workflow. And our proofing papers set the standard for color consistency. In short, everything we do is designed to add value to your vision.



555 Theodore Fremd Ave.  
Rye, NY 10580-1451  
800.765.9384  
[www.mitsubishiimaging.com](http://www.mitsubishiimaging.com)



Fuji Building  
2-3 Marunouchi 3-chome  
Chiyodaku, Tokyo 100-0005, Japan  
+81-3-3213-3741