

Graphic Whizard



NEW!



VividCoater DLG Spot Coater



VividCoater DLG 620AS

VividCoater™ DLG Series

470A / 470AS / 620A / 620AS

1 YEAR LIMITED WARRANTY

VividCoater™ DLG Series

DLG 470A

DLG 470AS

DLG 620A

DLG 620AS

DLG Spot Coater

Electrical	220-240V 1phase/60Hz /40A	220-240V 1phase/60Hz/60A	220-240V 3phase/60Hz/60A	220-240V 3phase/60Hz/75A	220-240V 3phase/60Hz/80A
Speed	up to 5500 sph	up to 5500 sph	up to 5500 sph	up to 5500 sph	up to 5500 sph
Max Stock Size	18.80"W(47cm) * 17.7"(45cm)	18.80"W(47cm) * 17.7"(45cm)	24.25"W(62cm) * 17.7"(45cm)	24.25"W(62cm) * 17.7"(45cm)	24.25"W(62cm) * 17.7"(45cm)
Stock Weight	80-350 gsm	80-350 gsm	80-350 gsm	80-350 gsm	80-350 gsm
Dimensions					
Length	130" (330 cm)	130" (330 cm)	130" (330 cm)	130" (330 cm)	118" (300 cm)
Width	47.25" (120 cm)	47.25" (120 cm)	47.25" (120 cm)	47.25" (120 cm)	44" (110 cm)
Height	49.25" (125 cm)	49.25" (125 cm)	49.25" (125 cm)	49.25" (125 cm)	55.25" (140 cm)
Weight	1875 lbs (850 kg)	2325 lbs (1050 kg)	2205 lbs (1000 kg)	2650 lbs (1200 kg)	2975 lbs (1350 kg)

Miscellaneous Information

- Standard with touch screen controls for easier use
- UV lamp (one standard, second optional)(Spot Coater comes with 2 standard)
- IR lamp as standard
- 3 rollers with reverse and variable roller speed ratio control provides best coating results
- Pneumatic automatic receding stacker on AS models and Spot Coater
- Air knife optional for assistance with thin stocks (above 80 gsm)

Note:

- All models require compressed air
- External ventilation or air purification highly recommended

Graphic Whizard inc.

Authorized Dealer:



5230 Finch Avenue East, Unit 6, Scarborough, ON M1S 4Z9
 (416)297-7996 • (800)608-4506
 www.pressdown.net • sales@pressdown.net