

MATERIAL SAFETY DATA SHEET

1. PRODUCT IDENTIFICATION

Trade Name: **Genie CleanPlate – GCP-300**
Generic Name: **Anti Toning Fountain Solution Additive**

Manufacturer: Pacific Products, Inc.
Distributor: **DAA International LLC**
Address: **24-L Commerce Road**
City, State, Zip: **Fairfield, NJ 07004**

Emergency Telephone: **209 267 9134**
Technical Telephone: **800 631 0039**

DOT Hazard Classification: **NOT REGULATED**
NFPA Codes: **Health: 1 Flammability: 0 Reactivity: 0**
HMIS Codes: **Health: 1 Flammability: 0 Reactivity: 0**

2. HAZARDOUS INGREDIENTS

If present, IARC, NTP and OSHA carcinogens & chemicals subject to the reporting requirements of SARA Title III, Section 313 are identified in this section.

| Ingredient Name: | CAS#: | %vol: | TWA/TLV: | SARA TITLE III |
|-------------------------------------|-------------|-------|----------|----------------|
| Dipropolyne Glycol Monomethyl Ether | 034590-94-8 | N/A | N/A | No |

Proprietary Ingredients:

THIS PRODUCT CONTAINS NO REPUTABLE HAZARDOUS INGREDIENTS.

References: 29CFR 1910.1200, ACDIH "Threshold Limit Values for Chemicals in the Workplace", National Toxicology Program Annual Report, International Agency for Research on Cancer Monograph & 40CFR Part 372. All components of this product are in compliance with TSCA.

3. PHYSICAL DATA

| | |
|---------------------------|---------------|
| Boiling Point @ 760mm Hg: | 212° F |
| Vapor Pressure @ 88 F: | >1% |
| Specific Gravity @ 68 F: | 1.01 |
| Evaporation Rate: | N/A |
| V.O.C.: | >4% 0.7#/gal) |
| Water Solubility: | Soluble |
| Appearance: | Clear Liquid |
| Odor: | Mild Odor |

4. FIRE & EXPLOSION DATA

Flash Point (method): **>200° F (TOC)**
Explosive Limit: **LEL – N/A UEL – N/A**
Extinguishing Media: **Foam or Dry Chemical**
Fire Fighting Procedure: **No specific requirements**
Flammability: **Inflammable in contact with flames or sparks**

5. HEALTH HAZARD DATA

EYES: Will cause irritation, redness, tearing and blurred vision. Contact lenses must not be worn when possibility exist for eye contact due to spraying liquids or airborne particles.

SKIN: Prolonged or repeated contact may cause slight irritation.

BREATHING: Excessive inhalation of vapors can cause slight nasal & respiratory irritation

SWALLOWING: Can cause gastrointestinal irritation, nausea, vomiting

EFFECT OF ACURE EXPOSURE TO MATERIAL: N/A

EFFECTS OF CHRONIC EXPOSURE TO MATERIAL: N/A

6. FIRST AID / EMERGENCY PROCEDURES

INHALATION: Remove to fresh air. If breathing is difficult, administer oxygen. If breathing has stopped, give artificial respiration.

SKIN CONTACT: Wash thoroughly with soap and water. Remove and launder contaminated clothing before re-use.

EYES: Flush with copious amounts of water. Get medical attention.

INGESTION: Do not induce vomiting. If large quantity is swallowed, give lukewarm water (pint).

NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON.

Get medical attention immediately. Risk of lung damage exceeds poisoning risk.

PRIMARY ENTRY ROUTE(S): Inhalation, skin contact.

CHRONIC HEALTH EFFECTS: Overexposure may aggravate existing skin, eye and lung condition.

7. REACTIVITY DATA

MATERIAL IS STABLE.

HAZARDOUS POLYMERIZATION CAN NOT OCCUR.

INCOMPATIBILITIES: Avoid contact with strong oxidizing materials, strong mineral acids, chlorine bleach.

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon mono/dioxides.

CONDITIONS TO AVOID: None known.

8. SPILL OR LEAK PRECEDURES

SMALL SPILLS: Absorb liquid on paper, vermiculite, floor absorbent or other absorbent material.

LARGE SIPLLS: Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed. Stop spill at source, prevent spill from spreading, pump liquid to salvage tank. Remaining liquid may be taken up on absorbent material and shoveled in to containers.

WASTE MANAGEMENT: Small or large spill: Dispose in accordance with local, state & federal regulations.

9. SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION: If workplace exposure limit(s) of product are exceeded, a NIOSH/MSHA approved air supply respirator is advised in absence of proper environmental control.

VENTILATION: Provide sufficient mechanical (general or local exhaust) ventilation to maintain minimum exposure.

EYE PROTECTION: Splash proof goggles are advised for operations where eye or face contact can occur.

GLOVES: Wear impervious gloves.

OTHER PROTECTIVE EQUIPMENT: To prevent repeated or prolonged skin contact, wear impervious clothing & gloves.

10. SPECIAL PRECAUTIONS

ALL HAZARD PRECAUTIONS GIVEN IN THE DATA SHEET MUST BE OBSERVED.

AS OF PREPARATION OF THIS DOCUMENT, THE FOREGOING INFORMATION IS BELIEVED TO BE ACCURATE AND IS PROVIDED IN GOOD FAITH TO COMPLY WITH APPLICABLE FEDERAL AND STATE LAW(S). HOWEVER, NO WARRANTY OR REPRESENTATION WITH RESPECT TO SUCH INFORMATION IS INTENDED OR GIVEN.

Date revised: 03/06/09